

# SKF GS 81230 thrust roller bearings

SKF GS 81230 thrust roller bearings Deal is 201.613 mm da 101.803 mm Ca your source for OEM and accessories. We sell Genuine at discount prices.

da	201.613 mm
Da	339.999 mm
Ca	101.803 mm
A1	190.5 mm
A2	273.05 mm
ba	80.169 mm
H	401.637 mm
H1	200.025 mm
H2	79.375 mm
J min.	549.275 mm
J max.	619.125 mm
J1	114.3 mm
L	711.2 mm
N1	34.925 mm
R1	120.65 mm
R2	42.069 mm
RG	1 NPT
PG	1/4 NPT
h	57.15 mm
Housing	SAF 044 KA
Bearing	23044 CCK/W33
Adapter sleeve assembly	SNW 3044×7.15/16

Stabilizing ring	2 x 36053-140
Labyrinth ring	2 x LOR 167
End plug (suffix Y)	EPR 23
Bearing limiting speed	2000 r/min
P60°	290 kN
P90°	173 kN
P120°	107 kN
P150°	94.3 kN
P180°	113 kN
Pa	59.6 kN
Mass pillow block	153 kg
Cap bolt	4 x 7/8-9 UNC
Cap bolt recommended tightening torque	271.2 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.25 in
Initial grease fill	1672.65 g