

SKF L 555249/210 tapered roller bearings

SKF L 555249/210 tapered roller bearings Cylindrical Bore Bore Type Manufacturers , Open Enclosure Online Wholesale Suppliers □ Double Row Configuration !

| | |
|-------------------------|---------------------|
| Bore Type | Cylindrical Bore |
| Enclosure | Open |
| Configuration | Double Row |
| Roller Profile | Symmetric |
| Center Guidance | Floating Steel Ring |
| Retainer Material | Pressed Steel |
| Nr. of Holes | 6 |
| Weight | 8.820 kg |
| d | 90 mm |
| D | 190 mm |
| B | 64 mm |
| Fillet Radius/Chamfer | 3 mm |
| Groove Width A | 11 mm |
| Hole Diameter (do) | 6 mm |
| Dynamic Load Rating | 745,000 N |
| Static Load Rating | 660,000 N |
| Limiting Speed – Grease | 2,600 rpm |
| Limiting Speed – Oil | 3,200 rpm |
| Constant e | 0.34 |
| Axial Load Factor Y0 | 1.96 |
| Axial Load Factor Y1 | 2.00 |
| Axial Load Factor Y2 | 2.98 |

| | |
|------------------|-------------------|
| Radial Clearance | 0.100 to 0.135 mm |
| da (min) | 104 mm |
| Da (max) | 176 mm |
| ra (max) | 2.5 mm |