

SKF LBCF 25 A-2LS linear bearings

Request A Quote 15 mm B For Your Special SKF LBCF 25 A-2LS linear bearings Needs Today! Free 40 mm d Quotes. ISO 9001 certified.

d	40 mm
D	68 mm
B	15 mm
rs min	1 mm
Radial clearance class	C4
Mass	0.19 kg
Dynamic load, C	16.8 kN
Static load, C ₀	11.5 kN
Fatigue limit load, C _u	0.52 kN
f ₀	15.2
N _{lim} (grease)	6,100 rpm
Min operating temperature, T _{min}	-25 °C
Max operating temperature, T _{max}	110 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.66 Hz
Characteristic outer ring frequency, BPF ₀	5.12 Hz
Characteristic inner ring frequency, BRFI	6.88 Hz
da min	45 mm
da max	47 mm

Da max	63 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.18
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C4-Extra Loose
Inch – Metric	Metric
Long Description	40MM Bore; 68MM Outside Diameter; 15MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania Prelubricat
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball

Weight / LBS	0.423
Outer Race Width	0.591 Inch 15 Millimeter
Bore	1.575 Inch 40 Millimeter
Outside Diameter	2.677 Inch 68 Millimeter
Inner Race Width	0 Inch 0 Millimeter