

SKF LM 742747/710 tapered roller bearings

SKF LM 742747/710 tapered roller bearings Warehouse offers car parts and car accessories. We sell discount online as well 30 mm d as cheap machinery parts.

d	30 mm
D	62 mm
B	16 mm
rs min	1 mm
Radial clearance class	C2
Mass	0.2 kg
Dynamic load, C	19.5 kN
Static load, C ₀	11.3 kN
Fatigue limit load, C _u	0.51 kN
f ₀	13.8
N _{lim} (grease)	11,000 rpm
Min operating temperature, T _{min}	-20 °C
Max operating temperature, T _{max}	120 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.68 Hz
Characteristic outer ring frequency, BPF ₀	3.58 Hz
Characteristic inner ring frequency, BPF _I	5.42 Hz
da min	35 mm
Da max	57 mm
ra max	1 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.198
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C2-Snug
Inch – Metric	Metric
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO
Other Features	Deep Groove Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.439
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter
Bore	1.181 Inch 30 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter