

SKF LM11949/910/Q tapered roller bearings

We Provide Extensive SKF LM11949/910/Q tapered roller bearings Selection And Competitive Wholesale Pricing. 28x58x17.25 Size (mm)

| | |
|-------------------------------|-------------|
| Size (mm) | 28x58x17.25 |
| Bore Diameter (mm) | 28 |
| Outer Diameter (mm) | 58 |
| Width (mm) | 17,25 |
| d | 28 mm |
| D | 58 mm |
| T | 17,25 mm |
| B | 16 mm |
| C | 14 mm |
| a | 13,2 mm |
| r min. | 1 mm |
| r1 min. | 1 mm |
| da min. | 37 mm |
| Da min | 50 mm |
| Da max. | 52 mm |
| db max. | 34 mm |
| Db min. | 55 mm |
| ra max. | 1 mm |
| rb max. | 1 mm |
| Weight | 0,203 Kg |
| Basic dynamic load rating (C) | 39,5 kN |
| Basic static load rating (C0) | 41,5 kN |

| | |
|----------------------------|------------|
| (Grease) Lubrication Speed | 6300 r/min |
| (Oil) Lubrication Speed | 9000 r/min |
| Calculation factor (e) | 0,35 |
| Calculation factor (Y0) | 0,93 |
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.1 |
| Product Group | B00308 |
| LangID | 1 |
| outer r | 1 |
| D_ | 58 |
| TC-BET22 | 0 |
| TC-BET21 | 4 |
| TC-BET23 | 0 |
| inner r | 1 |
| mass | 0.203 |
| GRS rpm | 6300 |
| D_b | 55 |
| Cr | 4050 |
| TC-RA | 116.082 |
| DE_ | 50.543 |
| T-ALP23 | 0 |
| db | 34 |
| T-ALP22 | 30 |
| Prod_Type3 | TRBSR_MD_A |
| da | 37 |
| T-ALP21 | 26 |
| Iso | — |

| | |
|----------|-------------|
| ALPHA_ | 13.25 |
| SDM_ | 43.024 |
| SBRG | 2 |
| D_a2 | 50 |
| hidYobi | HR302/28 |
| Y1 | 1.7 |
| D_a1 | 52 |
| B_ | 16 |
| hidTable | ecat_NSTPRM |
| Oil rpm | 9000 |
| C0r | 4200 |
| Y0 | 0.93 |
| TC-SLR | 11.2 |
| inner ra | 1 |
| outer rb | 1 |
| C0 | 41.5 |
| Sa | 2 |
| Sb | 3 |
| e | 0.35 |
| DA_ | 7.714 |
| Z_ | 15 |
| C_ | 14 |
| yobi | HR302/28 |
| TC-DA1 | 8.102 |
| TC-DA2 | 7.325 |
| KBRG | 3111 |
| DI_ | 35.505 |