

# SKF LTCD 40-2LS linear bearings

170 Million used 72 Outer Diameter (mm) SKF LTCD 40-2LS linear bearings instantly searchable. Shop our large selection of parts based 35x72x17 Size (mm) on brand, price, description, and location. Order the with stock ...

Size (mm)	35x72x17
Bore Diameter (mm)	35
Outer Diameter (mm)	72
Width (mm)	17
d	35 mm
D	72 mm
B	17 mm
C	17 mm
d1	46,9 mm
r1 min.	1,1 mm
r2 min.	1,1 mm
D2	62,7 mm
Weight	0,29 Kg
Temperature –	30 to +250 °
Basic static load rating (C0)	15,3 kN
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.302
EAN	7316571587974
Product Group	B00308

Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Polyalkylene Glycol/Graphite Mixture Filled
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	35MM Bore; 72MM Outside Diameter; 17MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO
Other Features	Deep Groove   Extreme Temperature Variant
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6207-2Z/VA201
Weight / LBS	0.3
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.669 Inch   17 Millimeter
Outside Diameter	2.835 Inch   72 Millimeter
Bore	1.378 Inch   35 Millimeter
bore diameter:	35 mm
precision rating:	Not Rated
outside diameter:	72 mm
finish/coating:	Uncoated

overall width:	17 mm
cage material:	Steel
bore type:	Round
outer ring width:	17 mm
closure type:	Double Shielded
fillet radius:	1.1 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm:	160 RPM
internal clearance:	C0
series:	62
operating temperature range:	-20 to +480 °F
resistance features:	Corrosion Resistant, Extreme Temperature
static load capacity:	15.3 kN
d1 ≈	46.94 mm
D2 ≈	62.69 mm
r1,2 min.	1.1 mm
da min.	42 mm
da max.	46.8 mm
Da max.	65 mm
ra max.	1 mm
Basic dynamic load rating C	27 kN
Basic static load rating C0	15.3 kN
Limiting speed	80 r/min
Limiting temperature T max.	250 °C
Mass bearing	0.3 kg