

# SKF LUCF 40 linear bearings

Find the discount SKF LUCF 40 linear bearings online you need . We offer 0.0 Inventory ... If N/A Minimum Buy Quantity you check out our large selection of SKF LUCF 40 linear bearings once .

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 34.958   |
| EAN                       | 0883450247764  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | V Lock   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22222  |
| Seals                     | Teflon Labyrinth   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Double Nut   SAF Style  |
| Long Description          | 4 Bolt Pillow Block; 4" Bore; 4-15/16" Base to Center Height; V Lock Mount; Spherical Roll |

|                               |                                 |
|-------------------------------|---------------------------------|
| UNSPSC                        | 31171511                        |
| Harmonized Tariff Code        | 8483.20.40.80                   |
| Noun                          | Bearing                         |
| Keyword String                | Pillow Block                    |
| Manufacturer Item Number      | QVVPH22V400ST                   |
| Weight / LBS                  | 87                              |
| Nominal Bolt Center to Center | 13.2 Inch   335.3 Millimeter    |
| Bolt Spacing Maximum          | 14.5 Inch   368.3Millimeter     |
| d                             | 4 Inch   101.6 Millimeter       |
| Bolt Spacing Minimum          | 11.875 Inch   301.625Millimeter |
| B                             | 4.938 Inch   125.425 Millimeter |
| D                             | 5.13 Inch   130.302 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter            |