

SKF N 1017 KTN9/HC5SP cylindrical roller bearings

Request A Quote 1000 mm d For Your Special SKF N 1017 KTN9/HC5SP cylindrical roller bearings Needs Today! Free Quotes. ISO 9001 103 mm B certified. 1320 mm D

| | |
|-----------------------------|-----------|
| d | 1000 mm |
| D | 1320 mm |
| B | 103 mm |
| d1 ≈ | 1126 mm |
| d2 ≈ | 1103 mm |
| D1 ≈ | 1195 mm |
| a | 458 mm |
| r1,2 min. | 6 mm |
| r3,4 min. | 6 mm |
| da min. | 1023 mm |
| Da max. | 1297 mm |
| Db max. | 1297 mm |
| ra max. | 5 mm |
| rb max. | 5 mm |
| Basic dynamic load rating C | 832 kN |
| Basic static load rating C0 | 2450 kN |
| Fatigue load limit Pu | 34.5 kN |
| Reference speed | 340 r/min |
| Limiting speed | 360 r/min |
| Calculation factor A | 86.5 |
| Calculation factor kr | 0.079 |
| Calculation factor e | 0.95 |

| | |
|-----------------------|--------|
| Calculation factor X | 0.37 |
| Calculation factor Y0 | 0.29 |
| Calculation factor Y2 | 0.66 |
| Mass bearing | 370 kg |