

SKF N311ECP cylindrical roller bearings

SKF N311ECP cylindrical roller bearings Product Brochures , 0.0 Inventory Manufacturing Service . Get Your Free.

| | |
|---------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 17.25 |
| EAN | 7316576668227 |
| Product Group | M06110 |
| Number of Mounting Holes | 2 |
| Mounting Method | Tapered Adapter Sleeve |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 3/4 Inch |
| Relubricatable | Yes |
| Insert Part Number | 1313 EK |
| Seals | Labyrinth |
| Housing Configuration | 2 Piece Split |
| Inch – Metric | Inch |
| Other Features | Double Row Medium Duty |
| Long Description | 2 Bolt Pillow Block; 2-3/16" Bore; 3-1/2" Base to Center Height; Tapered Adapter Sleeve Mo |

| | |
|-------------------------------|--------------------------------|
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | SAF 1613 |
| Weight / LBS | 38 |
| d | 2.188 Inch 55.575 Millimeter |
| Bolt Spacing Maximum | 11 Inch 279.4Millimeter |
| Nominal Bolt Center to Center | 10.3 Inch 260.5 Millimeter |
| Bolt Spacing Minimum | 9.625 Inch 244.475Millimeter |
| B | 3.5 Inch 88.9 Millimeter |
| D | 5.313 Inch 134.95 Millimeter |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |
| da | 55.563 mm |
| Da | 140 mm |
| Ca | 57.785 mm |
| A1 | 88.9 mm |
| A2 | 134.938 mm |
| ba | 32.544 mm |
| H | 167.481 mm |
| H1 | 88.9 mm |
| H2 | 31.75 mm |
| J min. | 244.475 mm |
| J max. | 279.4 mm |
| L | 330.2 mm |
| N1 | 22.225 mm |
| R1 | 53.181 mm |
| R2 | 21.431 mm |

| | |
|--|----------------|
| RG | 3/8 NPT |
| PG | 1/8 NPT |
| h | 36.513 mm |
| Housing | SAF 613 |
| Bearing | 1313 EKTN9 |
| Adapter sleeve assembly | SNW 113×2.3/16 |
| Stabilizing ring | 2 x SR-1613 |
| Labyrinth ring | 2 x LOR 32 |
| End plug (suffix Y) | EPR 7 |
| Bearing limiting speed | 6000 r/min |
| P60° | 83.2 kN |
| P90° | 49.8 kN |
| P120° | 30.2 kN |
| P150° | 26.7 kN |
| P180° | 31.6 kN |
| Pa | 6.49 kN |
| Mass pillow block | 17.1 kg |
| Cap bolt | 2 x 5/8-11 UNC |
| Cap bolt recommended tightening torque | 298.3 N·m |
| Cap bolt, SAE grade | 8 |
| Appropriate attachment bolt size G | 0.75 in |
| Initial grease fill | 175.77 g |