

# SKF N311ECP cylindrical roller bearings

SKF N311ECP cylindrical roller bearings Product Brochures , 0.0 Inventory Manufacturing Service . Get Your Free.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	17.25
EAN	7316576668227
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Tapered Adapter Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	1313 EK
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Double Row   Medium Duty
Long Description	2 Bolt Pillow Block; 2-3/16" Bore; 3-1/2" Base to Center Height; Tapered Adapter Sleeve Mo

UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SAF 1613
Weight / LBS	38
d	2.188 Inch   55.575 Millimeter
Bolt Spacing Maximum	11 Inch   279.4Millimeter
Nominal Bolt Center to Center	10.3 Inch   260.5 Millimeter
Bolt Spacing Minimum	9.625 Inch   244.475Millimeter
B	3.5 Inch   88.9 Millimeter
D	5.313 Inch   134.95 Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
da	55.563 mm
Da	140 mm
Ca	57.785 mm
A1	88.9 mm
A2	134.938 mm
ba	32.544 mm
H	167.481 mm
H1	88.9 mm
H2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
L	330.2 mm
N1	22.225 mm
R1	53.181 mm
R2	21.431 mm

RG	3/8 NPT
PG	1/8 NPT
h	36.513 mm
Housing	SAF 613
Bearing	1313 EKTN9
Adapter sleeve assembly	SNW 113×2.3/16
Stabilizing ring	2 x SR-1613
Labyrinth ring	2 x LOR 32
End plug (suffix Y)	EPR 7
Bearing limiting speed	6000 r/min
P60°	83.2 kN
P90°	49.8 kN
P120°	30.2 kN
P150°	26.7 kN
P180°	31.6 kN
Pa	6.49 kN
Mass pillow block	17.1 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	175.77 g