

# SKF NA 2206.2RSX cylindrical roller bearings

How do you find the SKF NA 2206.2RSX cylindrical roller bearings specification? Manufacturers 0.0 Inventory Online Free check☐

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 5.68  |
| EAN                       | 0662327029036   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Eccentric Collar  |
| Housing Style             | 4 Bolt Round Flange Cartridge   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 9/16 Inch   |
| Relubricatable            | Yes   |
| Insert Part Number        | YG239NL   |
| Seals                     | Single Lip Contact  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | With Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 4 Bolt Round Flange Cartridge; 2-7/16" Bore; 6-1/2" Bolt Circle; 4.6" Bolt Spacing; 1 |

|                                    |  |
|------------------------------------|--|
| Other Features                     | Single Row   Spherical   Standard Duty   Wide Inner Race |
| UNSPSC                             | 31171501   |
| Harmonized Tariff Code             | 8483.20.40.40  |
| Noun                               | Bearing  |
| Keyword String                     | Flanged  |
| Manufacturer Item Number           | FC3Y239N   |
| Manufacturer Internal Number       | 5802903  |
| Weight / LBS                       | 12.5   |
| Bolt Spacing                       | 4.6 Inch   117 Millimeter                                |
| D                                  | 3.063 Inch   77.8 Millimeter                             |
| Cartridge Pilot Depth              | 0.875 Inch   22.225 Millimeter                           |
| Cartridge Pilot Diameter           | 5.512 Inch   140 Millimeter                              |
| d                                  | 2.438 Inch   61.925 Millimeter                           |
| Nominal Bolt Circle Diameter Round | 6.5 Inch   165 Millimeter                                |