## SKF NCF2980CV cylindrical roller bearings

Various types and sizes to accommodate your 0.0 Inventory SKF NCF2980CV cylindrical roller bearings requirements. N/A Minimum Buy Quantity

| Inventory                 | 0.0   |
|---------------------------|---|
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 26.33   |
| EAN                       | 0793699906912   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Tapered Adapter Sleeve  |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 1 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 63110   |
| Seals                     | Heavy Contact   |
| Housing Configuration     | 1 Piece Solid   |
| Inch — Metric             | Inch  |
| Other Features            | Double Row  |
| Long Description          | 2 Bolt Pillow Block; 3-11/16"<br>Bore; 4-1/8" Base to Center<br>Height; Tapered Adapter Sleeve<br>M |

| UNSPSC                        | 31171511                        |
|-------------------------------|---------------------------------|
| Harmonized Tariff Code        | 8483.20.40.80                   |
| Noun                          | Bearing                         |
| Keyword String                | Pillow Block                    |
| Manufacturer Item Number      | MAS6311                         |
| Manufacturer Internal Number  | 190691                          |
| Weight / LBS                  | 58                              |
| В                             | 4.125 Inch   104.775 Millimeter |
| Bolt Spacing Maximum          | 0 Inch   OMillimeter            |
| Nominal Bolt Center to Center | 10.9 Inch   276.9 Millimeter    |
| d                             | 3.688 Inch   93.675 Millimeter  |
| Bolt Spacing Minimum          | 0 Inch   OMillimeter            |
| D                             | 5.969 Inch   151.613 Millimeter |
| Actual Bolt Center to Center  | 10.9 Inch   276.2Millimeter     |