

SKF NCF3068CV cylindrical roller bearings

100% Authentic. SKF NCF3068CV cylindrical roller bearings 225 Bore Diameter (mm) Highest 225x125x68 Size (mm) Quality. Certified Supplier.

Size (mm)	225x125x68
Bore Diameter (mm)	225
Outer Diameter (mm)	125
Width (mm)	68
d1	125 mm
D	225 mm
B	68 mm
d2	159 mm
d3	180 mm
D1	197 mm
B1	97 mm
B4	24 mm
b	8.3 mm
K	4.5 mm
r1,2 – min.	2.1 mm
da – max.	159 mm
db – min.	149 mm
Da – max.	213 mm
Ba – min.	8 mm
ra – max.	2 mm
Basic dynamic load rating – C	659 kN
Basic static load rating – C0	900 kN

Fatigue load limit – Pu	88 kN
Reference speed	2200 r/min
Limiting speed	2800 r/min
Calculation factor – e	0.28
Calculation factor – Y1	2.4
Calculation factor – Y2	3.6
d2 ≈	159 mm
D1 ≈	197 mm
r1,2 min.	2.1 mm
da max.	159 mm
db min.	149 mm
Da max.	213 mm
Ba min.	8 mm
ra max.	2 mm
Basic dynamic load rating C	659 kN
Basic static load rating C0	900 kN
Fatigue load limit Pu	88 kN
Calculation factor e	0.28
Calculation factor Y1	2.4
Calculation factor Y2	3.6
Calculation factor Y0	2.5
Mass bearing + sleeve	14.3 kg