

SKF NJ 2214 ECM thrust ball bearings

Shop SKF NJ 2214 ECM thrust ball bearings huge online discount inventory. and Import machinery parts 130x180x50 Size (mm) your car needs with Free Shipping and Free Extended Warranty.

| | |
|-------------------------------|------------|
| Size (mm) | 130x180x50 |
| Bore Diameter (mm) | 130 |
| Outer Diameter (mm) | 180 |
| Width (mm) | 50 |
| d | 130 mm |
| D | 180 mm |
| B | 50 mm |
| D1 | 162 mm |
| F | 146 mm |
| b | 5.5 mm |
| K | 3 mm |
| r1,2 – min. | 1.5 mm |
| r3,4 – min. | 1 mm |
| s | 2.2 mm |
| da – min. | 137 mm |
| da – max. | 144 mm |
| Da – max. | 172 mm |
| ra – max. | 1.5 mm |
| dn | 147 mm |
| Basic dynamic load rating – C | 187 kN |
| Basic static load rating – C0 | 390 kN |
| Fatigue load limit – Pu | 41.5 kN |

| | |
|---------------------------------------|--|
| Limiting speed for grease lubrication | 4300 r/min |
| Limiting speed for oil lubrication | 4800 mm/min |
| Gref | 31 cm |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 4.031 |
| EAN | 7316576611711 |
| Product Group | B04270 |
| Bore Profile | Tapered |
| Cage Material | Brass |
| Precision Class | Special Precision |
| Number of Rows of Rollers | Double Row |
| Separable | Inner Ring – Both Sides |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C1-Tight |
| Retainer | Yes |
| Relubricatable | Yes |
| Inch – Metric | Metric |
| Other Features | Plain Inner Ring 3 Rib Outer Ring High Precision Bearing Modified Internal Design Cage on Ou |

| | |
|---|--|
| Long Description | 130MM Bore; Tapered Bore Profile; 180MM Outside Diameter; 50MM Width; Brass Cage Material; Special |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| Manufacturer Item Number | NNU 4926 BK/SPW33 |
| Weight / LBS | 8.879 |
| Outside Diameter | 7.087 Inch 180 Millimeter |
| Width | 1.969 Inch 50 Millimeter |
| Bore | 5.118 Inch 130 Millimeter |
| r1,2 min. | 1.5 mm |
| r3,4 min. | 1 mm |
| s max. | 2.2 mm |
| da min. | 137 mm |
| da max. | 144 mm |
| Da max. | 172 mm |
| Basic dynamic load rating C | 187 kN |
| Basic static load rating C0 | 390 kN |
| Fatigue load limit Pu | 41.5 kN |
| Attainable speed for grease lubrication | 4300 r/min |
| Attainable speed for oil-air lubrication | 4800 r/min |
| Reference grease quantity Gref | 31 cm ³ |
| Static radial stiffness (guideline value) | 3570 N/μm |
| Mass bearing | 3.85 kg |