

SKF NJ 310 ECJ thrust ball bearings

With over 10170 full-service stores, our 45×36.512×29 Size (mm) SKF NJ 310 ECJ thrust ball bearings inventory is extensive and our parts are priced right. within 24 hours. This helps you 36,512 Outer Diameter (mm) maximize your 45 Bore Diameter (mm) productivity by saving time and your hard-earned dollars.

Size (mm)	45×36.512×29
Bore Diameter (mm)	45
Outer Diameter (mm)	36,512
Width (mm)	29
d	36.512 mm
A	45 mm
A1	29 mm
H	21 mm
H1	47.6 mm
H2	19 mm
L	160 mm
J	126 mm
N1	14 mm
B	42.9 mm
s1	25.4 mm
Basic dynamic load rating – C	25.5 kN
Basic static load rating – C0	15.3 kN
Limiting speed	160 r/min
Limiting temperature – T	350 °C
Mass bearing unit	1.47 kg

Grub (set) screw – G2 – 5/16-24 UNF	5/1624 UNF
Hexagonal key size for grub screw – H	3.969 mm
Recommended tightening torque for grub screw	6.5 N·m
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.54
EAN	7316571381114
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	YAR 207-107-2F/VA228
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Inch
Other Features	Single Row Standard Duty Wide Inner Race High Temperature Bearing with Graphite Has Flinger

Long Description	2 Bolt Pillow Block; 1-7/16" Bore; 1-7/8" Base to Center Height; Set Screw Mount; Ball Bea
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SY 1.7/16 TF/VA228
Weight / LBS	3.4
Bore	1.438 Inch 36.525 Millimeter
Length Thru Bore	1.688 Inch 42.87 Millimeter
Bolt Spacing Minimum	4.688 Inch 119.075Millimeter
Bolt Spacing Maximum	5.25 Inch 133.35Millimeter
Base to Center Height	1.875 Inch 47.63 Millimeter
Nominal Bolt Center to Center	5 Inch 127 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
N	21 mm
Basic dynamic load rating C	25.5 kN
Basic static load rating C0	15.3 kN
Limiting temperature T max.	350 °C
Grub (set) screw G2	5/16-24 UNF
Hexagonal key size for grub screw N	3.969 mm
Attachment bolts, recommended metric size G	12 mm
Bearing	YAR 207-107-2FW/VA228