

SKF NNCF4852CV cylindrical roller bearings

What is the best place to 200x130x69 Size (mm) buy 200 Bore Diameter (mm) SKF NNCF4852CV cylindrical roller bearings online? Manufacturing Service .

Size (mm)	200x130x69
Bore Diameter (mm)	200
Outer Diameter (mm)	130
Width (mm)	69
d	130 mm
D	200 mm
B	69 mm
d2	145 mm
D1	175 mm
b	6 mm
K	3 mm
r1,2 – min.	2 mm
da – min.	139 mm
Da – max.	191 mm
ra – max.	2 mm
Basic dynamic load rating – C	569 kN
Basic static load rating – C0	815 kN
Fatigue load limit – Pu	81.5 kN
Reference speed	2000 r/min
Limiting speed	3000 r/min
Calculation factor – e	0.31
Calculation factor – Y1	2.2

Calculation factor – Y2	3.3
Calculation factor – Y0	2.2
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	7.805
EAN	7316577119407
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Withdrawal Nut	Not Applicable
Inch – Metric	Metric
Long Description	130MM Straight Bore; 200MM Outside Diameter; 69MM Width; C0-Medium Clearance; Shaft Mount; Double Ro
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Weight / LBS	17.192
Width	2.717 Inch 69 Millimeter

Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
Bore	5.118 Inch 130 Millimeter
Outside Diameter	7.874 Inch 200 Millimeter
bore diameter:	130 mm
maximum rpm:	3000 RPM
outside diameter:	200 mm
operating temperature range:	Maximum of +390 °F
overall width:	69 mm
cage material:	Steel
bore type:	Straight
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	69 mm
dynamic load capacity:	540 kN
fillet radius:	2 mm
static load capacity:	815 kN
series:	240
d2 ≈	145 mm
D1 ≈	175 mm
r1,2 min.	2 mm
da min.	139 mm
Da max.	191 mm

ra max.	2 mm
Basic dynamic load rating C	569 kN
Basic static load rating C0	815 kN
Fatigue load limit Pu	81.5 kN
Calculation factor e	0.31
Calculation factor Y1	2.2
Calculation factor Y2	3.3
Calculation factor Y0	2.2
Mass bearing	8.05 kg