

# SKF NU 2026 ECMA thrust ball bearings

LET 0.0 Inventory OUR SKF NU 2026 ECMA thrust ball bearings  
SKF Manufacturer Name EXPERTS GET YOU THE PARTS YOU NEED. N/A  
Minimum Buy Quantity

|                      |                |
|----------------------|----------------|
| Inventory            | 0.0            |
| Manufacturer Name    | SKF            |
| Minimum Buy Quantity | N/A            |
| Weight               | 0              |
| Product Group        | M06110         |
| Bearing              | 23044 CC/W33   |
| Lock nut             | HM 3044        |
| Lock washer          | MS 3044        |
| Locating ring        | 2 x FRB 10/340 |
| da                   | 220 mm         |
| db                   | 235 mm         |
| Ca                   | 110 mm         |
| Da                   | 340 mm         |
| A                    | 260 mm         |
| A1                   | 190 mm         |
| H                    | 403 mm         |
| H1                   | 200 mm         |
| H2                   | 70 mm          |
| J                    | 580 mm         |
| L                    | 690 mm         |
| N                    | 50 mm          |
| N1                   | 42 mm          |

|   |                  |
|---|------------------|
| ba  | 89 mm            |
| bc  | 108 mm           |
| J6  | 644 mm           |
| J7  | 72 mm            |
| N4 max.   | 16 mm            |
| A2L   | 11.5 mm          |
| A2T   | 30.5 mm          |
| 2 x TSN 3044/235 S                                  | 2 x TNF 3044/235 |
| P55°  | 1700 kN          |
| P90°  | 1020 kN          |
| P120°   | 760 kN           |
| P150°   | 680 kN           |
| P180°   | 850 kN           |
| Pa  | 300 kN           |
| Q120°   | 1430 kN          |
| Q150°   | 825 kN           |
| Q180°   | 715 kN           |
| Mass housing  | 103 kg           |
| Cap bolt, size                                      | M 30 x 170       |
| Cap bolt, rec. tightening torque                    | 400 N·m          |
| Appropriate attachment bolt, size G                 | 36 mm            |
| Appropriate attachment bolt, rec. tightening torque | 2280 N·m         |
| Eye bolt, size                                      | M12              |
| Initial grease fill, 20%                            | 1500 g           |
| Initial grease fill, 40%                            | 2700 g           |
| Adapter sleeve                                      | 0H 3044 H        |
| 2 x TSN 3044 S                                      | 2 x TNF 3044 ET  |