

SKF NU 2312 ECM thrust ball bearings

SKF NU 2312 ECM thrust ball bearings with easy-to-use 6 Days or more Days to Ship parts graphics, giving you the ability to check parts availability, pricing, examine remanufactured options.

| | |
|-------------------------------------|---------------------------|
| Days to Ship | 6 Days or more |
| RoHS | 6 |
| Materials of Inner and Outer Ring | Steel |
| Bearing Style | Double Shielded |
| Outer Ring Type | Flat |
| d | 6 |
| Outer Diameter D(\emptyset) | 10 |
| B | 3 |
| Basic Load Rating Dynamic Rating(N) | 495 |
| Revolution Frequency(rpm) | 45000 |
| Rolling Element Material | Steel |
| Basic Load Rating Static Rating(N) | 218 |
| Sealing Structure | Double steel plate shield |
| Lubricant | NS Hairyu-bu Grease |
| Bearing Ring Shape | Ball |
| Precision | Grade 0 |
| Specifications/Environment | Standard |
| Load Direction | Radial |
| Number of Bearing Ring Rows | Single Row |
| Size Standard | Metric System |
| Internal Clearance Symbol | MC3 |

| | |
|-------------------------------------|-----------------|
| Inner/Outer Ring Material | [Steel] Steel |
| Outer Ring Shape | Flat |
| I.D.(Ø) | 6 |
| O.D.(Ø) | 10 |
| Width(mm) | 3 |
| Basic Dynamic Load Rating(N) | 495 |
| Max. Allowed rpm(rpm) | 45000 |
| Retainer Type | Punching |
| Basic Load Rating, Static Rating(N) | 218 |
| Clearance sign | CN (standard) |
| Accuracy(Class) | Class 0 |
| Acoustic Symbol | No |
| Holder Symbol | No |
| Symbol of Bearing Ring Shape | No |
| Seal, Shield Symbols | ZZ1 |
| Precision Grade Symbol | No |
| Special Configurations Code | No |
| Rubugado Symbol | No |
| Material Symbol | No |
| Spacer, Sleeve symbol | No |
| Types | No |
| Type | Ball |
| Specifications, Environment | Standard |
| Outer Ring | With Outer Ring |
| Number of Raceway Ring Rows | Single Row |
| Size Standards | Metric System |
| Combination symbol | No |
| Low Torque Specification | No |
| Internal Symbol | No |

| | |
|---------------|----|
| Torque Symbol | No |
|---------------|----|