

# SKF NU1028ML cylindrical roller bearings

High Quality SKF NU1028ML cylindrical roller bearings. Competitive Pricing. Accept Small Order. Easy and Fast 120 mm d 28 mm B Shipping.

d	120 mm
D	180 mm
B	28 mm
a min	3.45 mm
a max	3.71 mm
Ca min	6.45 mm
Ca max	6.81 mm
rs min	2 mm
rNs min	0.5 mm
D3 max	173.66 mm
b min	3.5 mm
b max	3.8 mm
r0 max	0.6 mm
D4 max	192.9 mm
f	3.1 mm
Snap ring reference	R180
Radial clearance class	CN
Mass	2.07 kg
Dynamic load, C	85 kN
Static load, C0	79.5 kN
Fatigue limit load, Cu	2.95 kN
f0	15.9

Nlim (grease)	3,500 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	8.1 Hz
Characteristic outer ring frequency, BPF0	6.59 Hz
Characteristic inner ring frequency, BRFI	8.41 Hz
da min	129 mm
Da max	171 mm
ra max	2 mm
rNa max	0.5 mm
Db min	195 mm