

SKF NUP 19/600 ECMA/HA1 thrust ball bearings

Our highly-skilled and factory-trained service experts have 7 Bore Diameter (mm) the resources to help you with all your SKF NUP 19/600 ECMA/HA1 thrust ball bearings needs – including 7x19x6 Size (mm) routine maintenance, major repairs, warranty service, and equipment inspections.

Size (mm)	7x19x6
Bore Diameter (mm)	7
Outer Diameter (mm)	19
Width (mm)	6
d	7 mm
D	19 mm
B	6 mm
C	6 mm
d1	11,1 mm
r1 min.	0,3 mm
r2 min.	0,3 mm
D1	15,2 mm
D2	16,5 mm
da min.	9 mm
Da max.	17 mm
rc max.	0,3 mm
Weight	0,0076 Kg
Basic dynamic load rating (C)	2,34 kN
Basic static load rating (C0)	0,95 kN
Fatigue load limit (Pu)	0,04

Reference speed	85000 r/min
Limiting speed	53000 r/min
Calculation factor (f0)	13
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.01
EAN	7316577662538
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	7MM Bore; 19MM Outside Diameter; 6MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Fi
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	607
Weight / LBS	0.02
Outside Diameter	0.748 Inch 19 Millimeter
Outer Race Width	0.236 Inch 6 Millimeter

Bore	0.276 Inch 7 Millimeter
bore diameter:	7 mm
static load capacity:	0.95 kN
outside diameter:	19 mm
precision rating:	ABEC 3 (ISO Class 6)
overall width:	6 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	6 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
snap ring included:	Without Snap Ring
maximum rpm:	53000 RPM
internal clearance:	C0
series:	60
dynamic load capacity:	2.34 kN
d1 ≈	11.1 mm
D2 ≈	16.5 mm
ra max.	0.3 mm
Basic dynamic load rating C	2.34 kN
Basic static load rating C0	0.95 kN
Fatigue load limit Pu	0.04 kN
Calculation factor kr	0.025
Calculation factor f0	13
Mass bearing	0.0076 kg