

SKF P 40 RM bearing units

The online SKF P 40 RM bearing units parts store gives you immediate access to a selection of more than 1.4 million new, used, remanufactured. 30x55x13 Size (mm)

Size (mm)	30x55x13
Bore Diameter (mm)	30
Outer Diameter (mm)	55
Width (mm)	13
d	30 mm
D	55 mm
B	13 mm
C	13 mm
r min.	1 mm
da min.	35 mm
Da max.	50 mm
ra max.	1 mm
Weight	0,116 Kg
Basic dynamic load rating (C)	13,2 kN
Basic static load rating (C0)	8,25 kN
(Grease) Lubrication Speed	13000 r/min
(Oil) Lubrication Speed	15000 r/min
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.125
Product Group	B00308
Enclosure	Open

Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	30MM Bore; 55MM Outside Diameter; 13MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6006
Weight / LBS	0.276
Bore	1.181 Inch 30 Millimeter
Outside Diameter	2.165 Inch 55 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
Bearing No.	6006
r(min)	1
Cr	16.5
C0r	8.25
Cu	0.530
f0	14.7
Grease lub.	13000
Oil lub.	15000
da(min)	35

Da(max)	50
ra(max)	1
(Refer.)Mass(kg)	0.116