

SKF P 45 TF bearing units

Welcome to the SKF P 45 TF bearing units N/A Minimum Buy Quantity online seller. 0.0 Inventory

| | |
|---------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | ABB MOTORS AND MECHANICAL INC |
| Minimum Buy Quantity | N/A |
| Weight | 19.881 |
| EAN | 0782475036509 |
| Product Group | M06288 |
| Number of Mounting Holes | 2 |
| Mounting Method | Tapered Adapter Sleeve |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Tapered Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 5/8 Inch |
| Relubricatable | Yes |
| Insert Part Number | DU-SD-204 |
| Seals | Dual Piston Ring Seal |
| Housing Configuration | 2 Piece Split |
| Inch – Metric | Inch |
| Other Features | Double Row Special Duty |
| Long Description | 2 Bolt Pillow Block; 2-1/4" Bore; 3-3/4" Base to Center Height; Tapered Adapter Sleeve Mou |
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.80 |

| | |
|-------------------------------|---------------------------------|
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | P2B-SD-204 SPECIAL DUTY |
| Manufacturer Internal Number | 066303 |
| Weight / LBS | 47 |
| Nominal Bolt Center to Center | 9.8 Inch 248.9 Millimeter |
| d | 2.25 Inch 57.15 Millimeter |
| Bolt Spacing Minimum | 9.125 Inch 231.775Millimeter |
| D | 4.563 Inch 115.9 Millimeter |
| Bolt Spacing Maximum | 10.375 Inch 263.525Millimeter |
| B | 3.75 Inch 95.25 Millimeter |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |