

# SKF PCM 19019560 M plain bearings

SKF PCM 19019560 M plain bearings Manufacturers 0.0 Inventory , Online Wholesale Suppliers !

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 174.79   |
| EAN                       | 0782475223299  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Adapter Sleeve   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 1 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | INS-IP-608R  |
| Seals                     | Triple Lip Contact   |
| Housing Configuration     | 2 Piece Split  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Has Flinger   |
| Long Description          | 4 Bolt Pillow Block; 6-1/2" Bore; 7-1/2" Base to Center Height; Adapter Sleeve Mount; Sphe |

|                               |                                 |
|-------------------------------|---------------------------------|
| UNSPSC                        | 31171511                        |
| Harmonized Tariff Code        | 8483.20.40.80                   |
| Noun                          | Bearing                         |
| Keyword String                | Pillow Block                    |
| Manufacturer Item Number      | P4B536-ISAF-608RE               |
| Manufacturer Internal Number  | 037916                          |
| Weight / LBS                  | 385                             |
| Bolt Spacing Minimum          | 20.875 Inch   530.225Millimeter |
| Bolt Spacing Maximum          | 23.625 Inch   600.075Millimeter |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter            |
| d                             | 6.5 Inch   165.1 Millimeter     |
| D                             | 7.391 Inch   187.731 Millimeter |
| B                             | 7.5 Inch   190.5 Millimeter     |
| Nominal Bolt Center to Center | 22.3 Inch   565.2 Millimeter    |