

# SKF PCM 303420 M plain bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all your SKF PCM 303420 M plain bearings TIMKEN Manufacturer Name needs – 0.0 Inventory including routine maintenance, major repairs, warranty service, and equipment inspections.

|                                 |                 |
|---------------------------------|-----------------|
| Inventory                       | 0.0             |
| Manufacturer Name               | TIMKEN          |
| Minimum Buy Quantity            | N/A             |
| Weight                          | 0.02 Kg         |
| EAN                             | 0087796292369   |
| Product Group                   | B00308          |
| Enclosure                       | 2 Seals         |
| Precision Class                 | ABEC 1   ISO P0 |
| Maximum Capacity / Filling Slot | No              |
| Rolling Element                 | Ball Bearing    |
| Snap Ring                       | No              |
| Internal Special Features       | No              |
| Cage Material                   | Steel           |
| Enclosure Type                  | Contact Seal    |
| Internal Clearance              | C0-Medium       |
| Inch – Metric                   | Metric          |
| UNSPSC                          | 31171504        |
| Harmonized Tariff Code          | 8482.10.50.68   |
| Noun                            | Bearing         |
| Keyword String                  | Ball            |

|                          |                            |
|--------------------------|----------------------------|
| Weight / LBS             | 0.057                      |
| Inner Race Width         | 0.315 Inch   8 Millimeter  |
| D                        | 1.102 Inch   28 Millimeter |
| Outer Race Width         | 0.315 Inch   8 Millimeter  |
| d                        | 0.472 Inch   12 Millimeter |
| Clearance                | C0 (Normal)                |
| Bore Size d              | 12 mm                      |
| Features                 | Contact Seals              |
| Outside Diameter D       | 28.0000 mm                 |
| Outside Ring Width B     | 8.000 mm                   |
| Radius Rs min            | 0.300 mm                   |
| Cr – Dynamic Load Rating | 5.1 kN                     |
| C0r – Static Load Rating | 2.4 kN                     |
| Grease Reference Speed   | 23000 rpm                  |
| Oil Reference Speed      | 33000 rpm                  |