

SKF PCMW 325401.5 E plain bearings

Various types and sizes 73.025 mm da to accommodate your SKF PCMW 325401.5 E plain bearings requirements.

da	73.025 mm
Da	150 mm
Ca	42.799 mm
A1	88.9 mm
A2	127 mm
ba	31.75 mm
H	180.975 mm
H1	95.25 mm
H2	31.75 mm
J min.	250.825 mm
J max.	279.4 mm
L	330.2 mm
N1	22.225 mm
R1	53.975 mm
R2	22.225 mm
RG	3/8 NPT
PG	1/8 NPT
h	36.513 mm
Housing	SAF 517
Bearing	1217 K
Adapter sleeve assembly	SNW 17×2.7/8
Stabilizing ring	2 x SR-1517
Labyrinth ring	2 x LOR 52

End plug (suffix Y)	EPR 9
Bearing limiting speed	5600 r/min
P60°	84.5 kN
P90°	50.7 kN
P120°	31.6 kN
P150°	28.5 kN
P180°	34.7 kN
Pa	7.12 kN
Mass pillow block	17.9 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	218.29 g