

SKF PCZ 4032 E plain bearings

SKF PCZ 4032 E plain bearings Warehouse offers car parts and car accessories. We sell discount online as well as 20 Outer Diameter (mm) cheap machinery 32x20x7 Size (mm) parts.

Size (mm)	32x20x7
Bore Diameter (mm)	32
Outer Diameter (mm)	20
Width (mm)	7
d	20 mm
D	32 mm
B	7 mm
d2	22.6 mm
D2	29.52 mm
r1,2 – min.	0.3 mm
da – min.	22 mm
da – max.	22.5 mm
Da – max.	30.5 mm
ra – max.	0.3 mm
Basic dynamic load rating – C	3.1 kN
Basic static load rating – C0	2.1 kN
Fatigue load limit – Pu	0.09 kN
Limiting speed	13000 r/min
Calculation factor – kr	0.02
Calculation factor – f0	13.3
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A

Weight / Kilogram	0
EAN	7316570620474
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Stainless Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	20MM Bore; 32MM Outside Diameter; 7MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No F
Other Features	Deep Groove NBR Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	W 61804-2RS1
Weight / LBS	0.043
Bore	0.787 Inch 20 Millimeter
Outer Race Width	0.276 Inch 7 Millimeter
Outside Diameter	1.26 Inch 32 Millimeter
Inner Race Width	0 Inch 0 Millimeter
d2 ≈	22.6 mm
D2 ≈	29.52 mm

r _{1,2} min.	0.3 mm
d _a min.	22 mm
d _a max.	22.5 mm
D _a max.	30.5 mm
r _a max.	0.3 mm
Basic dynamic load rating C	3.12 kN
Basic static load rating C ₀	2.08 kN
Fatigue load limit P _u	0.09 kN
Calculation factor k _r	0.02
Calculation factor f ₀	13.3
Mass bearing	0.017 kg