

SKF PF 1.1/2 TR bearing units

Our highly-skilled and factory-trained service experts have the resources to help you 750 Outer Diameter (mm) with all your SKF PF 1.1/2 TR bearing units needs – including routine maintenance, major repairs, 500x750x150 Size (mm) warranty service, and equipment inspections.

Size (mm)	500x750x150
Bore Diameter (mm)	500
Outer Diameter (mm)	750
Width (mm)	150
d	500 mm
D	750 mm
T	150 mm
d1	725 mm
r min.	6 mm
A	280 mm
B1	51 mm
B2	144 mm
C	74 mm
D1	611 mm
da min.	615 mm
Da max.	670 mm
ra max.	5 mm
Weight	231 Kg
Basic dynamic load rating (C)	4700 kN
Basic static load rating (C0)	22600 kN
Bore Type	Cylindrical Bore
Enclosure	Open

Configuration	Single Row
Bore Size	500 mm
Outside Diameter	750 mm
Fillet Radius/Chamfer	6 mm
Width	150 mm
Dynamic Load Rating	4,700,000 N
Static Load Rating	22,600,000 N
Limiting Speed – Oil	410 rpm
B	51 mm
da (min)	615 mm
Da (max)	670 mm
ra (max)	5 mm