

SKF PWKR 72.2RS cylindrical roller bearings

offers a SKF PWKR 72.2RS cylindrical roller bearings selection of Genuine at Wholesale Prices. We are a 0.0 Inventory SKF Manufacturer Name SKF PWKR 72.2RS cylindrical roller bearings Certified Parts Retailer

| | |
|---------------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 17.54 |
| EAN | 7316570369267 |
| Product Group | B00152 |
| Enclosure | Open |
| Flush Ground | No |
| Rolling Element | Ball Bearing |
| Number of Rows of Balls | Double Row |
| Precision Class | ABEC 3 ISO P6 |
| Maximum Capacity / Filling Slot | No |
| Snap Ring | No |
| Cage Material | Steel |
| Contact Angle | 32 Degree |
| Internal Clearance | C0-Medium |
| Number of Bearings | 1 (Single) |
| Inch – Metric | Metric |
| Long Description | 110MM Bore; 240MM Outside Diameter; 92.1MM Width; Open; No Flush Ground; Ball Bearing; Double Row of |

| | |
|-------------------------------|--------------------------|
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact |
| Manufacturer Item Number | 3322 A |
| Weight / LBS | 38.625 |
| B | 92.1 mm |
| d | 110 mm |
| D | 240 mm |
| bore diameter: | 110 mm |
| radial static load capacity: | 305 kN |
| outside diameter: | 240 mm |
| cage material: | Metal |
| overall width: | 3.6250 in |
| outer ring width: | 92.1 mm |
| contact angle: | 35 ° |
| maximum rpm: | 2600 RPM |
| row type & fill slot: | Double-Row Non-Fill Slot |
| finish/coating: | Uncoated |
| internal clearance: | C0 |
| precision rating: | Not Rated |
| closure type: | Open |
| fillet radius: | 2.5 mm |
| radial dynamic load capacity: | 291 kN |
| series: | 33 |
| d1 ≈ | 152.99 mm |
| D1 ≈ | 200.01 mm |
| r1,2 min. | 3 mm |
| a | 142 mm |

| | |
|-----------------------------|------------|
| da min. | 124 mm |
| Da max. | 226 mm |
| ra max. | 2.5 mm |
| Basic dynamic load rating C | 291 kN |
| Basic static load rating C0 | 305 kN |
| Fatigue load limit Pu | 9.8 kN |
| Reference speed | 3000 r/min |
| Limiting speed | 2600 r/min |
| Calculation factor kr | 0.07 |
| Calculation factor e | 0.8 |
| Calculation factor X | 0.63 |
| Calculation factor Y0 | 0.66 |
| Calculation factor Y1 | 0.78 |
| Calculation factor Y2 | 1.24 |
| Mass bearing | 19 kg |