

SKF RNA0 65x85x30 cylindrical roller bearings

SKF RNA0 65x85x30 cylindrical roller bearings SEARCH – 130 mm d Whether it's agriculture or construction equipment your working on, Has the you need.

d	130 mm
D	230 mm
B	40 mm
E	204 mm
F	156 mm
rs min	3 mm
r1s min	3 mm
Radial clearance class	C3
Mass (without HJ ring)	6.85 kg
Dynamic load, C	270 kN
Static load, C0	340 kN
Fatigue limit load, Cu	34.8 kN
Nlim (oil)	3,400 rpm
Nlim (grease)	2,900 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	7.37 Hz
Characteristic outer ring frequency, BPF0	7.37 Hz

Characteristic inner ring frequency, BPF1	9.63 Hz
da min	143 mm
da max	151 mm
db min	158 mm
Da max	217 mm
ra max	2.5 mm
r1a max	2.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	6.87
EAN	4547359142846
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID

Long Description	130MM Bore; Straight Bore Profile; 230MM Outside Diameter; 40MM Width; Brass Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NU226G1C3
Weight / LBS	15.138
Width	1.575 Inch 40 Millimeter
Outside Diameter	9.055 Inch 230 Millimeter
Bore	5.118 Inch 130 Millimeter