

SKF RNU 2212 ECP cylindrical roller bearings

Shop SKF RNU 2212 ECP cylindrical roller bearings huge online discount inventory. and Import machinery parts your car needs with Free Shipping and 115x90x13 Size (mm) Free Extended 90 Outer Diameter (mm) Warranty.

Size (mm)	115x90x13
Bore Diameter (mm)	115
Outer Diameter (mm)	90
Width (mm)	13
d	90 mm
D	115 mm
B	13 mm
d1	98.3 mm
D2	109.5 mm
r1,2 – min.	1 mm
da – min.	94.6 mm
da – max.	98.1 mm
Da – max.	110 mm
ra – max.	1 mm
Basic dynamic load rating – C	19.5 kN
Basic static load rating – C0	17 kN
Fatigue load limit – Pu	0.915 kN
Reference speed	11000 r/min
Limiting speed	5600 r/min
Calculation factor – kr	0.015
Calculation factor – f0	13.4

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.303
EAN	7316577121721
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	90MM Bore; 115MM Outside Diameter; 13MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0;
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	61818 2RZ
Weight / LBS	0.67
Outside Diameter	4.528 Inch 115 Millimeter
Bore	3.543 Inch 90 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
bore diameter:	90 mm

static load capacity:	22 kN
outside diameter:	115 mm
precision rating:	Not Rated
overall width:	13 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
outer ring width:	13 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1 mm
internal clearance:	C0
maximum rpm:	5600 RPM
operating temperature range:	-40 to +210 °F
series:	61
dynamic load capacity:	19.5 kN
d1 ≈	98.3 mm
D2 ≈	109.5 mm
r1,2 min.	1 mm
da min.	94.6 mm
da max.	98.1 mm
Da max.	110 mm
ra max.	1 mm
Basic dynamic load rating C	19.5 kN
Basic static load rating C0	17 kN
Fatigue load limit Pu	0.915 kN
Calculation factor kr	0.015
Calculation factor f0	13.4
Mass bearing	0.29 kg