

# SKF SYJ 2. TF bearing units

How do N/A Minimum Buy Quantity you find the SKF SYJ 2. TF bearing units specification? 0.0 Inventory REXNORD Manufacturer Name Manufacturers Online Free check

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 2.13   |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1/2 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | UG224NL  |
| Seals                     | Single Lip Contact   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Single Row   Standard Duty   Standard Backing   Wide Inner Race                            |
| Long Description          | 2 Bolt Pillow Block; 1-1/2" Bore; 2" Base to Center Height; Set Screw Mount; Ball Bearing; |
| UNSPSC                    | 31171511   |

|                               |                               |
|-------------------------------|-------------------------------|
| Harmonized Tariff Code        | 8483.20.40.40                 |
| Noun                          | Bearing                       |
| Keyword String                | Pillow Block                  |
| Manufacturer Item Number      | P3U224NM4                     |
| Manufacturer Internal Number  | 5801435                       |
| Weight / LBS                  | 4.7                           |
| Actual Bolt Center to Center  | 5.4 Inch   136Millimeter      |
| d                             | 1.5 Inch   38.1 Millimeter    |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter          |
| D                             | 1.906 Inch   48.42 Millimeter |
| Nominal Bolt Center to Center | 5.4 Inch   136 Millimeter     |
| B                             | 2 Inch   50.8 Millimeter      |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter          |