

# SKF VKBA 1445 wheel bearings

170 0.0 Inventory Million used SKF VKBA 1445 wheel bearings instantly searchable. Shop our large selection N/A Minimum Buy Quantity of parts based on brand, price, description, and location. Order the with stock ...

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REGAL BELOIT  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 40.18   |
| EAN                       | 0662461371954   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Adapter Sleeve  |
| Housing Style             | 4 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 3/4 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | USI5000A-315  |
| Seals                     | Felt Labyrinth  |
| Housing Configuration     | 2 Piece Split   |
| Inch – Metric             | Inch  |
| Other Features            | Double Row   Has Flinger  |
| Long Description          | 4 Bolt Pillow Block; 3-15/16" Bore; 4-15/16" Base to Center Height; Adapter Sleeve Mount; |
| UNSPSC                    | 31171511  |

|                               |                                 |
|-------------------------------|---------------------------------|
| Harmonized Tariff Code        | 8483.20.40.80                   |
| Noun                          | Bearing                         |
| Keyword String                | Pillow Block                    |
| Manufacturer Item Number      | USRB5522AE-315                  |
| Manufacturer Internal Number  | 739805                          |
| Weight / LBS                  | 88.5                            |
| Bolt Spacing Maximum          | 14.5 Inch   368.3Millimeter     |
| B                             | 4.938 Inch   125.425 Millimeter |
| D                             | 5.938 Inch   150.825 Millimeter |
| d                             | 3.938 Inch   100.025 Millimeter |
| Nominal Bolt Center to Center | 13.5 Inch   342.5 Millimeter    |
| Bolt Spacing Minimum          | 12.594 Inch   319.888Millimeter |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter            |