## SKF W 627 XR deep groove ball bearings

High Quality 0.0 Inventory SKF W 627 XR deep groove ball bearings. Competitive Pricing. Accept Small Order. Easy and Fast Shipping. REGAL BELOIT Manufacturer Name

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | REGAL BELOIT   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 142.1  |
| EAN                       | 0662461353509  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | USI5000-515  |
| Seals                     | Felt Labyrinth   |
| Housing Configuration     | 2 Piece Split  |
| Inch — Metric             | Inch   |
| Other Features            | Double Row   Has Flinger   With<br>Set Screw   |
| Long Description          | 4 Bolt Pillow Block; 5-15/16"<br>Bore; 7-1/16" Base to Center<br>Height; Concentric Collar Mount |

| UNSPSC                           | 31171511                        |
|----------------------------------|---------------------------------|
| Harmonized Tariff Code           | 8483.20.40.80                   |
| Noun                             | Bearing                         |
| Keyword String                   | Pillow Block                    |
| Manufacturer Item Number         | USRB5534-515                    |
| Manufacturer Internal<br>Number  | 738184                          |
| Weight / LBS                     | 313                             |
| Actual Bolt Center to<br>Center  | 0 Inch   OMillimeter            |
| Bolt Spacing Maximum             | 21.625 Inch   549.275Millimeter |
| d                                | 5.938 Inch   150.825 Millimeter |
| D                                | 9.781 Inch   248.437 Millimeter |
| Nominal Bolt Center to<br>Center | 20.5 Inch   520.7 Millimeter    |
| Bolt Spacing Minimum             | 19.375 Inch   492.125Millimeter |
| В                                | 7.063 Inch   179.4 Millimeter   |