## SKF W 629-2RZ deep groove ball bearings

SKF W 629-2RZ deep groove ball bearings Manufacturers , Online Wholesale Suppliers ! Mounted Bearing Engineering Group 3-3/4 in Shaft Size

| Engineering Group       | Mounted Bearing         |
|-------------------------|-------------------------|
| Shaft Size              | 3-3/4 in                |
| Shaft Size Type         | Imperial                |
| Full Timken Part Number | QVF22V312SB             |
| Locking Style           | Single V-Lock           |
| Weight                  | 55 lb                   |
| Housing Style           | Four-Bolt Square Flange |
| UPC Code                | 0883450091701           |
| Dimension BC            | 10.96 in                |
| Dimension C             | 5.5 in                  |
| Dimension D             | 8.820 in                |
| Dimension E             | 7.75 in                 |
| Dimension F             | 9.97 in                 |
| Dimension H             | 1.50 in                 |
| Dimension J (Bolt Size) | 0.875 in                |
| Dimension L             | 4.49 in                 |
| Dimension L Exp         | 4.57 in                 |
| Dimension L Fix         | 4.49 in                 |
| Dimension N             | 4.060 in                |
| Dimension RV            | 0.36 in                 |
| Dimension SV            | 4.13 in                 |
| CO — Static Load        | 147000 lb               |

| C — Dynamic Load (Basic)            | 125000 lb |
|-------------------------------------|-----------|
| e — Geometry Factor                 | 0.26      |
| Y1 - Geometry Factor                | 2.55      |
| Y2 - Geometry Factor                | 3.80      |
| Oil Lubrication — M/N Seal          | 900 rpm   |
| Oil Lubrication — T Seal            | 1700 rpm  |
| Oil Lubrication — B/C/O Seal        | 600 rpm   |
| Grease Lubrication — M/N Seal       | 900 rpm   |
| Grease Lubrication — T Seal         | 1200 rpm  |
| Grease Lubrication — B/C/O Seal     | 600 rpm   |
| Float                               | 0.083 in  |
| Shaft Tolerance                     | 0.0030 in |
| Eng Internal Radial Clearance — Min | 0.0053    |
| Eng Internal Radial Clearance — Max | 0.0067    |
| Pre Install Clearance Min           | 0.0043 in |
| Pre Install Clearance Max           | 0.0055 in |