

SL014856 INA 280x350x69mm Other Features Full Complement | 3 Rib Inner Ring | 2 Rib Outer Ring | Operating Temperature From -30 to 120 Deg Cylindrical roller bearings

| | |
|---------------------------|------------------------------------|
| Category | Cylindrical Roller Bearings |
| BDI Inventory | 1.0 |
| Manufacturer Name | SCHAEFFLER GROUP |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 19.18 |
| EAN | 4054364122751 |
| Product Group – BDI | B04144 |
| Bore Profile | Straight |
| Cage Material | None |
| Precision Class | RBEC 1 ISO P0 |
| Number of Rows of Rollers | Double Row |
| Separable | No |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C0-Medium |
| Retainer | No |

| | |
|--------------------------|--|
| Relubricatable | Yes |
| Inch – Metric | Metric |
| Other Features | Full Complement 3 Rib Inner Ring 2 Rib Outer Ring Operating Temperature From -30 to 120 Deg |
| Long Description | 280MM Bore; Straight Bore Profile; 350MM Outside Diameter; 69MM Width; RBEC 1 ISO P0; Double Row; Not Separable; No Snap Ring; Relubricatable; C0-Medium Internal Clearance; No Retainer |
| Category – BDI | Cylindrical Roller Bearing |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| Manufacturer URL | http://www.ina.com |
| Manufacturer Item Number | SL014856 |
| Weight / LBS | 42.24 |
| Outside Diameter | 13.78 Inch 350 Millimeter |
| Width | 2.717 Inch 69 Millimeter |
| Bore | 11.024 Inch 280 Millimeter |
| Bearing number | SL014856 |
| Size (mm) | 280x350x69 |
| Brand | INA |
| Bore Diameter (mm) | 280 |
| Outer Diameter (mm) | 350 |
| Width (mm) | 69 |
| d | 280 mm |
| D | 350 mm |
| B | 69 mm |

| | |
|------------------|--|
| C | 34.5 mm |
| D ₁ | 326.4 mm |
| d ₁ | 306.8 mm |
| r _{min} | 2 mm |
| | NNC4856V / Designation to DIN 5412 |
| m | 16 kg / Weight |
| C _r | 700000 N / Dynamic load rating (radial) |
| C _{0r} | 1820000 N / Static load rating (radial) |
| C _{ur} | 198000 N / Fatigue limit load. radial |
| n _G | 980 1/min / Limiting speed |