

SL024930 INA UNSPSC 31171547 150x210x60mm Cylindrical roller bearings

| | |
|---------------------|--|
| Bearing number | SL024930 |
| Size (mm) | 150x210x60 |
| Brand | INA |
| Bore Diameter (mm) | 150 |
| Outer Diameter (mm) | 210 |
| Width (mm) | 60 |
| d | 150 mm |
| D | 210 mm |
| B | 60 mm |
| C | 30 mm |
| d ₁ | 171.8 mm |
| E | 192.77 mm |
| r _{min} | 2 mm |
| s | 4 mm / Axial displacement |
| | NNCL4930V / Designation to DIN 5412 |
| m | 6.45 kg / Weight |
| C _r | 410000 N / Dynamic load rating (radial) |
| C _{0r} | 820000 N / Static load rating (radial) |
| C _{ur} | 104000 N / Fatigue limit load. radial |
| n _G | 1790 1/min / Limiting speed |
| Category | Cylindrical Roller Bearings |

| | |
|---------------------------|--|
| BDI Inventory | 0.0 |
| Manufacturer Name | SCHAEFFLER GROUP |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 6.46 |
| EAN | 4012802424621 |
| Product Group – BDI | B04144 |
| Bore Profile | Straight |
| Cage Material | None |
| Precision Class | RBEC 1 ISO P0 |
| Number of Rows of Rollers | Double Row |
| Separable | Outer Ring – Both Sides |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C0-Medium |
| Retainer | No |
| Relubricatable | Yes |
| Inch – Metric | Metric |
| Other Features | Full Complement 3 Rib Inner Ring Plain Outer Ring Operating Temperature From -30 to 120 Deg |
| Long Description | 150MM Bore; Straight Bore Profile; 210MM Outside Diameter; 60MM Width; RBEC 1 ISO P0; Double Row; Outer Ring – Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Internal Clearance; No Retainer |
| Category – BDI | Cylindrical Roller Bearing |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |

| Noun | Bearing |
|--------------------------|---|
| Manufacturer URL | http://www.ina.com |
| Manufacturer Item Number | SL024930A |
| Weight / LBS | 14.22 |
| Bore | 5.906 Inch 150 Millimeter |
| Width | 2.362 Inch 60 Millimeter |
| Outside Diameter | 8.268 Inch 210 Millimeter |