

SL045013-PP INA Snap Ring Yes 65x100x46mm Cylindrical roller bearings

Bearing number	SL045013-PP
Size (mm)	65x100x46
Brand	INA
Bore Diameter (mm)	65
Outer Diameter (mm)	100
Width (mm)	46
d	65 mm
D	100 mm
B	46 mm
	30 ° / Chamfer angle
C	45 mm
C ₁	40.2 mm / Tolerance: +0.2
C _{a1} – 35 mm / Mounting dimension for snap ring WRE / Tolerance: -0,2	35 mm / Mounting dimension for snap ring WRE / Tolerance: 0.2
C _{a2} – 34 mm / Mounting dimension for retaining ring to DIN 471 / Tolerance: -0,2	34 mm / Mounting dimension for retaining ring to DIN 471 / Tolerance: 0.2
D ₁	97.4 mm / Tolerance: +0.2
d ₁	78.8 mm
d ₂	84 mm
d ₃	109 mm / Outside diameter of snap ring WRE

m	3.2 mm
r_{min}	0.6 mm
t	1 mm
X	36 mm / Distance between rolling elements
m	1.33 kg / Weight
C_r	130000 N / Dynamic load rating (radial)
C_{0r}	215000 N / Static load rating (radial)
C_{ur}	29500 N
$n_{G\ Fett}$	1600 1/min / Limiting speed for grease lubrication
	WRE100 / Designation for snap ring WRE
Category	Cylindrical Roller Bearings
BDI Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4012802071511
Product Group – BDI	B04144
Bore Profile	Straight
Cage Material	None
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Double Row
Separable	No
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring

Snap Ring	Yes
Internal Clearance	C0-Medium
Retainer	No
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Full Complement 3 Rib Inner Ring 1 Rib Outer Ring Seals on Both Sides Operating Temperature From -20 to 80 Deg
Long Description	65MM Bore; Straight Bore Profile; 100MM Outside Diameter; 46MM Width; RBEC 1 ISO P0; Double Row; Not Separable; Snap Ring; Relubricatable; C0-Medium Internal Clearance; No Retainer
Category – BDI	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.ina.com
Manufacturer Item Number	SL045013PP
Weight / LBS	3.511
Bore	2.559 Inch 65 Millimeter
Outside Diameter	3.937 Inch 100 Millimeter
Width	1.811 Inch 46 Millimeter