

SL182980 INA 400x540x82mm Internal Clearance C0-Medium Cylindrical roller bearings

| | |
|---------------------|---|
| Bearing number | SL182980 |
| Size (mm) | 400x540x82 |
| Brand | INA |
| Bore Diameter (mm) | 400 |
| Outer Diameter (mm) | 540 |
| Width (mm) | 82 |
| d | 400 mm |
| D | 540 mm |
| B | 82 mm |
| D ₁ | 496.1 mm |
| d ₁ | 450 mm |
| E | 510.85 mm |
| r _{min} | 4 mm |
| s | 5 mm / Axial displacement |
| m | 54.3 kg / Weight |
| C _r | 1710000 N / Dynamic load rating (radial) |
| C _{0r} | 3500000 N / Static load rating (radial) |
| C _{ur} | 355000 N / Fatigue limit load. radial |
| n _G | 650 1/min / Limiting speed |
| Category | Cylindrical Roller Bearings |
| BDI Inventory | 0.0 |

| | |
|---------------------------|--|
| Manufacturer Name | SCHAEFFLER GROUP |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 65.08 |
| Product Group – BDI | B04144 |
| Bore Profile | Straight |
| Cage Material | None |
| Precision Class | RBEC 1 ISO P0 |
| Number of Rows of Rollers | Single Row |
| Separable | No |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C0-Medium |
| Retainer | No |
| Relubricatable | Yes |
| Inch – Metric | Metric |
| Other Features | Full Complement 2 Rib Inner Ring 1 Rib Outer Ring with Retaining Ring Operating Temperature From -30 to 120 Deg |
| Long Description | 400MM Bore; Straight Bore Profile; 540MM Outside Diameter; 82MM Width; RBEC 1 ISO P0; Single Row; Not Separable; No Snap Ring; Relubricatable; C0-Medium Internal Clearance; No Retainer |
| Category – BDI | Cylindrical Roller Bearing |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |

| | |
|--------------------------|---|
| Manufacturer URL | http://www.ina.com |
| Manufacturer Item Number | SL182980 |
| Weight / LBS | 143.352 |
| Outside Diameter | 21.26 Inch 540 Millimeter |
| Width | 3.228 Inch 82 Millimeter |
| Bore | 15.748 Inch 400 Millimeter |