

Slewing Bearing with External Gear or Internal Gear 232.21.0575.013

How do I place 8 Days or more Days to Ship an EMERGENCY order for a Slewing Bearing with External Gear or Internal Gear 232.21.0575.013 that I 6 RoHS 110 I.D.(Ø) want to pick up at a our store?

| | |
|--------------------------------------|----------------|
| Days to Ship | 8 Days or more |
| RoHS | 6 |
| I.D.(Ø) | 110 |
| O.D.(Ø) | 240 |
| Width(mm) | 50 |
| Number of Raceway Ring Rows | Single Row |
| Size Standards | Metric System |
| Outer Ring Type | Flat |
| Retainer Type | Momi removing |
| Rotational Speed(rpm) | 2600 |
| Basic Load Rating, Dynamic Rating(N) | 380000 |
| Basic Load Rating, Static Rating(N) | 435000 |
| Clearance sign | No |
| Accuracy(Class) | Class 0 |
| Bearing Ring Type | NF Type |
| Acoustic Symbol | No |
| Holder Symbol | M |
| Symbol of Bearing Ring Shape | No |
| Seal, Shield Symbols | No |
| Precision Grade Symbol | No |

| | |
|-------------------------------|--------------------|
| Symbol of contact angle | No |
| Special Configurations Code | No |
| Symbols of Lubrication Amount | No |
| Internal Symbol | No |
| Raceway Ring Shape | Cylindrical Roller |
| Load Direction | Radial |
| Inner/Outer Ring Material | Steel |
| Outer Ring | With Outer Ring |
| Precision (JIS) | Grade 0 |
| Specifications | Standard |
| Rolling Element Material | Steel |
| Holder Color | No |
| Low Torque Specification | No |
| Material Symbol | No |