

Slewing Bearing with External Gear or Internal Gear

232.21.0775.013

Manufacturers of all are represented in our partial list of clients. Contact N/A Minimum Buy Quantity Gary for a complete Slewing Bearing with External Gear or Internal Gear 232.21.0775.013 list of clients and projects. 0.0 Inventory

| | |
|---------------------------|----------------------------|
| Inventory | 0.0 |
| Manufacturer Name | IPTCI BEARINGS |
| Minimum Buy Quantity | N/A |
| Weight | 4.27 |
| Product Group | M06110 |
| Number of Mounting Holes | 4 |
| Mounting Method | Set Screw |
| Housing Style | 4 Bolt Square Flange Block |
| Rolling Element | Ball Bearing |
| Housing Material | Nickel Coated Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 5/8 Inch |
| Relubricatable | Yes |
| Insert Part Number | SUC212-39 |
| Seals | B Seal |
| Housing Configuration | 1 Piece Solid |
| Pilot Configuration | No Pilot |
| Inch – Metric | Inch |

| | |
|---------------------------------------|---|
| Long Description | 4 Bolt Square Flange Block; 2-7/16" Bore; 7.9" Bolt Circle; 5-5/8" Bolt Spacing; 1 Pi |
| Other Features | Single Row Spherical Corrosion Resistant Stainless Steel Insert Has Slinger Optional Locki |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Flanged |
| Manufacturer Item Number | SUCNPF 212 39 |
| Weight / LBS | 9.4 |
| d | 2.438 Inch 61.925 Millimeter |
| D | 2.563 Inch 65.09 Millimeter |
| Bolt Spacing | 5.625 Inch 142.88 Millimeter |
| Cartridge Pilot Depth | 0 Inch 0 Millimeter |
| Cartridge Pilot Diameter | 0 Inch 0 Millimeter |
| Nominal Bolt Circle Diameter Round | 7.9 Inch 200 Millimeter |