

Slewing Ring Bearing with External Gear for Crane Exvacators

What is Slewing Ring Bearing with External Gear for Crane Exvacators in mechanical engineering? Manufacturing N/A Minimum Buy Quantity Service . Upload your CAD 0.0 Inventory file for an TIMKEN Manufacturer Name instant.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	1.001 lb
EAN	0087796056251
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Eccentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/8 Inch
Relubricatable	Yes
Insert Part Number	G1008KRRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid
Inch – Metric	Inch

Other Features	Single Row Spherical Normal Duty High Base With Set Screw
Long Description	2 Bolt Pillow Block; 1/2" Bore; 1-3/16" Base to Center Height; Eccentric Collar Mount; Bal
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	RAS 1/2
Weight / LBS	1
Nominal Bolt Center to Center	3.6 Inch 92 Millimeter
D	1.469 Inch 37.3 Millimeter
Bolt Spacing Minimum	0 Inch 0Millimeter
Actual Bolt Center to Center	3.6 Inch 92Millimeter
d	0.5 Inch 12.7 Millimeter
B	1.188 Inch 30.175 Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Shaft Size d	1/2 in
Bearing Type	Ball Bearing
Inside Ring Outside Diameter	0.531 in
Dimension T	0.594 in
Series	Industrial
Seal Type	Shroud Seal
Base to Center Height H	30.16 mm
Total Length L	123.8 mm
Total Width A	1.189 in
Bolt Hole Spacing J	92.1 mm
Bolt Hole Width N	11.1 mm

Bolt Hole Length N1	22.2 mm
Foot Height H1	11.9 mm
Total Height H2	56.4 mm
Dimension L1	41.3 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm
Center of Bearing from End S	13.9 mm
Dimension B1	1.469 in
Static Load Rating	1070 lbf
Dynamic Load Rating	2380 lbf