

SNFA BS 275 /S 7P62U thrust ball bearings

SNFA BS 275 /S 7P62U thrust ball bearings Industries and Applications ? We sell discount online as well as cheap machinery 98.425 mm da parts.

da	98.425 mm
Da	200 mm
Ca	62.89 mm
A1	120.65 mm
A2	165.1 mm
S	4.763 mm
ba	50.006 mm
H	244.475 mm
H1	125.425 mm
H2	52.388 mm
L	419.1 mm
R1	67.866 mm
R2	31.75 mm
RG	3/8 NPT
PG	1/4 NPT
h	45.244 mm
Housing	SSAFS 522
Bearing	22222 EK
Adapter sleeve assembly	SNW 22×3.7/8
Stabilizing ring	SR-22-19
Labyrinth ring	2 x LOR 108
End plug (suffix Y)	EPR 13

Bearing limiting speed	4000 r/min
P60°	178 kN
P90°	107 kN
P120°	66.7 kN
P150°	59.6 kN
P180°	72.5 kN
Pa	17.3 kN
Mass pillow block	54 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	232.47 g