## SNFA BSQU 230/1 TDT thrust ball bearings

Enjoy N/A Minimum Buy Quantity High 0.0 Inventory Margins on Competitive Pricing.Great Wholesale Products at Low Costs.

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 14.528   |
| EAN                       | 0883450017947  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 4 Bolt Round Flange Cartridge  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22218  |
| Seals                     | Double Lip Viton   |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | With Pilot   |
| Inch — Metric             | Inch   |
| Long Description          | <pre>4 Bolt Round Flange Cartridge;<br/>3-1/2" Bore; 8.6" Bolt Circle;<br/>6.1" Bolt Spacing; 1 Pi</pre> |

| Other Features                        | Double Row   Double Collar  <br>With Set Screw |
|---------------------------------------|--|
| UNSPSC                                | 31171501                                       |
| Harmonized Tariff Code                | 8483.20.40.80                                  |
| Noun                                  | Bearing  |
| Keyword String                        | Flanged  |
| Weight / LBS                          | 32   |
| D                                     | 5.18 Inch   131.572 Millimeter                 |
| Cartridge Pilot Diameter              | 7.375 Inch   187.32 Millimeter                 |
| Nominal Bolt Circle Diameter<br>Round | 8.6 Inch   218.4 Millimeter                    |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter                          |
| d                                     | 3.5 Inch   88.9 Millimeter                     |
| Bolt Spacing                          | 6.1 Inch   154.9 Millimeter                    |