

SNFA E 220 7CE3 angular contact ball bearings

What is SNFA E 220 7CE3 angular contact ball bearings in mechanical engineering? Manufacturing 190 mm Da 73.787 mm Ca Service . Upload your 79.375 mm da CAD file for an instant.

da	79.375 mm
Da	190 mm
Ca	73.787 mm
A1	111.125 mm
A2	231.775 mm
ba	42.069 mm
H	230.981 mm
H1	120.65 mm
H2	50.8 mm
J min.	304.8 mm
J max.	342.9 mm
J1	57.15 mm
L	393.7 mm
N1	22.225 mm
R1	73.025 mm
R2	28.575 mm
RG	3/8 NPT
PG	1/4 NPT
h	50.8 mm
Housing	SAF 618
Bearing	1318 K
Adapter sleeve assembly	SNW 18×3.1/8

Stabilizing ring	2 x SR-1618
Taconite seal	TER 187
End plug (suffix Y)	EPR 11
Max. speed for Taconite seal	950 r/min
P60°	128 kN
P90°	77 kN
P120°	48.9 kN
P150°	44.5 kN
P180°	54.3 kN
Pa	11.6 kN
Mass pillow block	41.1 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	481.95 g