

SNFA HX85 /S 7CE3 angular contact ball bearings

SNFA HX85 /S 7CE3 angular contact ball bearings Industries and Applications ? We sell discount 62 Outer Diameter (mm) online as well as cheap 40x62x15 Size (mm) machinery parts.

Size (mm)	40x62x15
Bore Diameter (mm)	40
Outer Diameter (mm)	62
Width (mm)	15
d	40 mm
D	62 mm
T	15 mm
B	15 mm
C	12 mm
ra1 max.	0,6 mm
a	11,5 mm
r min.	0,6 mm
r1 min.	0,6 mm
da min.	44,5 mm
Da min	54 mm
Da max.	57,5 mm
db max.	45,5 mm
Db min.	58,5 mm
ra max.	0,6 mm
Sa	3 mm
Sb	3 mm
Weight	0,161 Kg

Basic dynamic load rating (C)	32,5 kN
Basic static load rating (C0)	48 kN
(Grease) Lubrication Speed	5 900 r/min
(Oil) Lubrication Speed	7 800 r/min
Calculation factor (e)	0,29
Calculation factor (Y0)	1,14
rs min	0.6 mm
r1s min	0.6 mm
e	0.29
Y2	2.07
Y0	1.14
Mass	0.16 kg
ISO 355 reference	T2BC040
Dynamic load, C	32.5 kN
Rating life coefficient, A2	1
Static load, C0	48 kN
Fatigue limit load, Cu	5.9 kN
Nlim (oil)	7,800 rpm
Nlim (grease)	5,900 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
da max	44.5 mm
db min	45.5 mm
Da max	57.5 mm
Db min	58.5 mm
ra max	0.6 mm
r1a max	0.6 mm
Inventory	10.0
Manufacturer Name	NTN

Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359529753
Product Group	B04336