

SNFA VEB 20 /S/NS 7CE3 angular contact ball bearings

100% 50 Bore Diameter (mm) Authentic. SNFA VEB 20 /S/NS 7CE3 angular contact ball bearings Highest Quality. Certified 50x90x30.2 Size (mm) Supplier.

Size (mm)	50x90x30.2
Bore Diameter (mm)	50
Outer Diameter (mm)	90
Width (mm)	30.2
d	50 mm
D	90 mm
B	30.2 mm
C	30.2 mm
Angle (α)	30 °
r min.	1.1 mm
Weight	0.670 Kg
Basic dynamic load rating (C)	54,5 kN
Basic static load rating (C0)	44,5 kN
(Grease) Lubrication Speed	5000 r/min
Inventory	1.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0.672
EAN	4991893601800
Product Group	B00152
Enclosure	Open
Flush Ground	No

Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	20 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	50MM Bore; 90MM Outside Diameter; 30.2MM Width; Open; No Flush Ground; Ball Bearing; Double Row of B
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	5210 BNLS
Weight / LBS	1.48
Bore	1.969 Inch 50 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
Width	1.189 Inch 30.2 Millimeter
Configuration	Double Row
Bore Type	Cylindrical Bore
Bore Size	50 mm
Fillet Radius/Chamfer	1.1 mm
Dynamic Load Rating	54,500 N
Static Load Rating	44,500 N
Limiting Speed – Grease	5,000 rpm

Limiting Speed – Oil	6,700 rpm
Radial Clearance	0.006 to 0.023 mm
da	57 mm83 mm
Dx	98 mm
ra	1 mm
Cy	5.4 mm