

# SNR 22310EAW33 spherical roller bearings

Find the discount SNR 22310EAW33 spherical roller bearings online you need 200x310x132 Size (mm) . We offer ... If you check out our large selection of SNR 22310EAW33 spherical roller bearings once .

|                                       |             |
|---------------------------------------|-------------|
| Size (mm)                             | 200x310x132 |
| Bore Diameter (mm)                    | 200         |
| Outer Diameter (mm)                   | 310         |
| Width (mm)                            | 132         |
| d                                     | 200 mm      |
| D                                     | 310 mm      |
| H                                     | 132 mm      |
| d1                                    | 263.9 mm    |
| 2C                                    | 66 mm       |
| r1,2 – min.                           | 2.1 mm      |
| r3,4 – min.                           | 1 mm        |
| da – min.                             | 236 mm      |
| Da – min.                             | 291 mm      |
| Da – max.                             | 292 mm      |
| ra – max.                             | 2 mm        |
| rb – max.                             | 1 mm        |
| Basic dynamic load rating – C         | 238 kN      |
| Basic static load rating – C0         | 865 kN      |
| Fatigue load limit – Pu               | 25.5 kN     |
| Limiting speed for grease lubrication | 1900 r/min  |
| Limiting speed for oil lubrication    | 2400 mm/min |

|  |                       |
|--|-----------------------|
| Preload                                  | 1525 N                |
| Static Axial rigidity                    | 1395 N/micron         |
| Gref                                     | 157.1 cm              |
| r1,2 min.                                | 2.1 mm                |
| r3,4 min.                                | 1 mm                  |
| da min.                                  | 236 mm                |
| Da min.                                  | 291 mm                |
| Da max.                                  | 292 mm                |
| ra max.                                  | 2 mm                  |
| rb max.                                  | 1 mm                  |
| Basic dynamic load rating C              | 238 kN                |
| Basic static load rating C0              | 865 kN                |
| Fatigue load limit Pu                    | 25.5 kN               |
| Attainable speed for grease lubrication  | 1900 r/min            |
| Attainable speed for oil-air lubrication | 2400 r/min            |
| Static axial stiffness                   | 1395 N/ $\mu$ m       |
| Reference grease quantity Gref           | 157.1 cm <sup>3</sup> |
| Mass bearing                             | 30.9 kg               |