

SNR 33011VC12 tapered roller bearings

SNR 33011VC12 tapered roller bearings Product Brochures 20 Bore Diameter (mm) , Manufacturing Service . Get Your Free.

| | |
|--|---|
| Bore Diameter (mm) | 20 |
| Outer Diameter (mm) | 23 |
| Bearing Type | straight |
| Shaft Dia., Nominal (d) | 20.0000 |
| Shaft Size (ds) – 20 +0 / -0/033 | 20 +0 / 0/033 |
| Housing Bore Dia. (Dh) – 23 +0.021 / -0 | 23 +0.021 / 0 |
| Bearing Outside Diameter, Nominal(Do) | 23.000 |
| Bearing Outside Diameter Tolerance (Do tol.) | 23.075 / 23.035 |
| Bearing Bore after Mounting (di) | 20.131 / 20.050 |
| Average Clearance (Cd) | 0.1070 |
| Wall Thickness (S3) | 1.460 |
| Bearing Length, Nominal (B) | 30.000 |
| Bearing Length Tolerance (B tol.) – +0 / -0.40 | +0 / 0.40 |
| OD Chamfer Length (Co) | 0.700 |
| ID Chamfer Angle (B deg.) | 30 |
| ID Chamfer Length (Ci) | 0.500 |
| Lube Hole Dia. (dl) | 4.000 |
| Material | Carbon steel shell with POM plastic liner |