

SNR 5212NRZZG15 angular contact ball bearings

Question SNR 5212NRZZG15 angular contact ball bearings 24 mm B ? Find what you need 90 mm d faster by entering your information .

| | |
|---|-----------|
| d | 90 mm |
| D | 140 mm |
| B | 24 mm |
| rs min | 1.5 mm |
| Radial clearance class | CN |
| Mass | 1.02 kg |
| Dynamic load, C | 58 kN |
| Static load, C ₀ | 49.5 kN |
| Fatigue limit load, C _u | 2.1 kN |
| f ₀ | 15.6 |
| N _{lim} (grease) | 4,700 rpm |
| Min operating temperature, T _{min} | -25 °C |
| Max operating temperature, T _{max} | 110 °C |
| Characteristic cage frequency, FTF | 0.43 Hz |
| Characteristic rolling element frequency, BSF | 7.49 Hz |
| Characteristic outer ring frequency, BPF ₀ | 6.08 Hz |
| Characteristic inner ring frequency, BRF ₀ | 7.92 Hz |
| da min | 98 mm |
| da max | 102 mm |

| | |
|---------------------------------|--|
| Da max | 132 mm |
| ra max | 1.5 mm |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 1.166 |
| Product Group | B00308 |
| Enclosure | 2 Seals |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Enclosure Type | Non-Contact Seal |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |
| Long Description | 90MM Bore; 140MM Outside Diameter; 24MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No |
| Other Features | Deep Groove Non-Friction Nitrile Rubber Seal |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Weight / LBS | 1.175 |
| Outside Diameter | 5.512 Inch 140 Millimeter |

| | |
|------------------|----------------------------|
| Inner Race Width | 0 Inch 0 Millimeter |
| Bore | 3.543 Inch 90 Millimeter |
| Outer Race Width | 0.945 Inch 24 Millimeter |