

SNR 7005HVDUJ74 angular contact ball bearings

What 170x280x109 Size (mm) are the types of SNR 7005HVDUJ74 angular contact ball bearings ? Manufacturing Service . Get Your Free, Instant price, design 170 Bore Diameter (mm) review.

| | |
|-------------------------------|-------------|
| Size (mm) | 170x280x109 |
| Bore Diameter (mm) | 170 |
| Outer Diameter (mm) | 280 |
| Width (mm) | 109 |
| d | 170 mm |
| D | 280 mm |
| B | 109 mm |
| C | 109 mm |
| r min. | 2,1 mm |
| da min. | 182 mm |
| da max | 190 mm |
| Da min | 239 mm |
| Da max. | 268 mm |
| ra max. | 2 mm |
| Weight | 26,6 Kg |
| Basic dynamic load rating (C) | 1080 kN |
| Basic static load rating (C0) | 1860 kN |
| (Grease) Lubrication Speed | 1000 r/min |
| (Oil) Lubrication Speed | 1300 r/min |
| Calculation factor (e) | 0,37 |
| Calculation factor (Y0) | 1,8 |

| | |
|---------------------------|--|
| Calculation factor (Y2) | 2,7 |
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 26.6 |
| Product Group | B04311 |
| Internal Clearance | C0-Medium |
| Mounting Method | Shaft Mount |
| Rolling Element | Spherical Roller Bearing |
| Bore Profile | Straight |
| Cage Material | Steel |
| Enclosure | Open |
| Number of Rows of Rollers | Double Row |
| Relubricatable | Yes |
| Withdrawal Sleeve | Not Applicable |
| Inch – Metric | Metric |
| Long Description | 170MM Straight Bore; 280MM Outside Diameter; 109MM Width; C0-Medium Clearance; Shaft Mount; Double R |
| UNSPSC | 31171510 |
| Harmonized Tariff Code | 84823080 |
| Noun | Bearing |
| Keyword String | Spherical |
| Manufacturer Item Number | 24134CE4 |
| Weight / LBS | 26.6 |
| Bore | 6.693 Inch 170 Millimeter |
| Adapter Part Number | Not Applicable Inch Not Applicable Millimeter |
| Outside Diameter | 11.024 Inch 280 Millimeter |

| | |
|------------|-----------------------------|
| Width | 4.291 Inch 109 Millimeter |
| Y3 | 1.8 |
| hidYobi | 24134CE4 |
| LangID | 1 |
| Y1 | 1.8 |
| D_ | 280 |
| Y2 | 2.7 |
| Macha rpm | 0 |
| B_ | 109 |
| da min | 182 |
| hidTable | ecat_NSSPHR |
| Oil rpm | 1300 |
| Y0 | 1.8 |
| mass | 26.6 |
| GRS rpm | 1000 |
| ra | 2 |
| TSR rpm | 1200 |
| C0 | 1860 |
| DE_ | 252.459 |
| X0 | 1 |
| Prod_Type3 | SRB_CTB_CB |
| X1 | 1 |
| X2 | 0.67 |
| SIR | 43.5 |
| e | 0.37 |
| DA_ | 28 |
| bomp | 24134CE4 |
| Z_ | 21 |
| ALP2 | 50 |

| | |
|---------|----------|
| ALP1 | 13 |
| ALP3 | 0 |
| D_a max | 268 |
| D_a min | 239 |
| yobi | 24134CE4 |
| ALPHA_ | 0.241 |
| SDM_ | 225.271 |
| r | 2.1 |
| KBRG | 2322 |
| SBRG | 41 |
| DI_ | 198.083 |